



CFMA-15L-OH



CFM-25L-OH

## Click Flowmeters

These click style Oxygen and Air flowmeters were designed for use in ambulances, hospitals and portable oxygen systems; there is no flow adjustment, just precise metered flow. Just Click it!

## Features

- Available in four configurations: 0-4 LPM, 0-8 LPM, 0-15 LPM and 0-25 LPM
- Dual units for multi-patient use from one oxygen outlet
- Low profile design
- Large, easy to read numbers
- Optional Power Take-off
- Rugged, impact resistant aluminum body
- Light weight
- 5 Year Warranty

## Specifications

Calibrated	Inlet pressure 50 PSIG / 70°F (21°C)
Operating Temperatures	20°F to 130°F (-28.8°C to 54.4°C)
Inlet Port	1/8 FNPT
Outlet Port	9/16-18 UNF (CGA 1240)
Storage Temperature	14°F to 125°F (-10°C to 51.6°C)
Material	Aluminum Body
Fixed Orifice Disk	Brass
Seal O-Ring	Rubber
Knob	ABS Plastic
Filter	25 microns stainless steel mesh screen

## Part Numbers

	Catalog Number	Flow Settings	
Oxygen	CFM-4	0; 0.03; 0.06; 0.12; 0.25; 0.5; 0.75; 1; 1.5; 2; 3; 4.	First, select the flow range.
	CFM-8	0; 0.5; 1; 1.5; 2; 2.5; 3; 4; 5; 6; 7; 8.	
	CFM-15	0; 0.5; 1; 2; 3; 4; 5; 6; 8; 10; 12; 15.	
	CFM-25	0; 0.5; 1; 2; 4; 5; 6; 8; 10; 15; 20; 25.	
Air	CFMA-15	0; 0.5; 1; 2; 3; 4; 5; 6; 7; 8; 10; 15.	

## Fittings

00	No Fitting (1/8" NPT Female)	Then, select the inlet fitting.
OH	Ohio Quick-Connect	
DS	DISS Female Nut & Nipple	
CH	Chemetron Quick-Connect	
PB	Puritan-Bennett Quick-Connect	
DH	DISS Hand-Tight	Finally, select any accessories.
P	Power Take-Off (Oxygen DISS with Check, up to 70 LPM flow)	
L	Security Cable, 6"	

Example: CFM-15OH is a click flowmeter 0-15LPM with an Ohio fitting on the back. CFM-25DSPL is a 0-25LPM flowmeter with a DISS fitting, power take-off and security cable.